




BlackBerry 7100g Battery Terminal Replacement

Written By: Kellen



INTRODUCTION

This guide describes how to replace the battery contact terminal, where the BlackBerry 7100g battery connects to the phone.



TOOLS:

- [Spudger](#) (1)
 - [T6 Torx Screwdriver](#) (1)
 - [iFixit Opening Tools](#) (1)
-

Step 1 — Battery




- Turn over your BlackBerry 7100g so that the back cover is facing up.
- Locate the battery cover release button near the bottom of the back panel.

Step 2




- Push down on the release button with one thumb.
- Slide the battery cover off with the other thumb.

Step 3




- Remove the battery from the battery housing by flipping up the top of the battery.

Step 4 — Housing



- Locate the silver strip near the top of your BlackBerry.
- Use a plastic opening tool to pry off the edge of the silver lining.
- Slide the tool along the length of the silver strip to completely remove it.

Step 5



i Do not lose the screws. They are quite small and can easily be misplaced.

- Locate and unscrew the four (4) screws using a T6 screwdriver.

Step 6



i The keypad cover may fall out of the housing when prying the housing apart.

- Tightly pinch the top of the front and back halves of the housing.
- Carefully pry the two halves of the housing apart.

Step 7






- You can now easily remove the "guts" of the phone from the housing.

Step 8 — Battery Terminal



- Remove the four screws holding the battery and speaker housing to the motherboard.

Step 9



- Once the battery housing is separated from the motherboard, the battery terminal will slide off the battery housing.

i The small plastic piece with four metal pins is the battery terminal shown in the third picture.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-06-28 02:00:22 AM.